

Double Business EVSE w/ Display



- » Lightweight and anti-uv treatment polycarbonate case provide 3 year's yellow resistance
- » 7" LCD screen
- » Integrated with any OCPP1.6J (Compatible with OCPP2.0.1)
- » ISO/IEC 15118 plug and charge
- » Firmware updated locally or by OCPP remotely
- » Optional wired/wireless connection for back office management
- » Optional RFID card reader for user identification and management
- » IK10 & Nema Type3R(IP65) enclosure for indoor & outdoor use
- » Restart button
- » Wall or pole mounted to suit the situation

Applications

- » Highway gas/service station
- » EV infrastructure operators and service providers
- » Parking garage
- » EV rental operator
- » Commercial fleet operators
- » EV dealer workshop
- » Residential



LEVEL 2 EV CHARGER



Model No.	LP-DS300/48A*2
Input Vol	208-240Vac
Frequency	60Hz
Amperage	48A+48A (Variable charging rate)
Max.Power Output	11.5kW*2
Gross Weight	22.0LBS
Package Dimension	20.1"*13.8"*13.8"
Protection	
Charging Interface	SAE J1772 Type 1 Plug
Safety	UL 2594, UL2231-1/-2
Protections	UVP, OVP, RCD(CCID 20), SPD, Ground Fault Protection, OCP, OTP, Control Pilot Fault Protection
Enviromental	
Operating Temperature	-30C to 50C
Relative Humidity	Up to 95% non-condensing
Cable Length	25ft Standard